SDS No: G_F125009_E_HP6

Safety Data Sheet (SDS)

Date prepared/revised: 2024/03/14

Section 1: Product and Company Identification

Product Name: CELPURGE

(Grade Name)

NX-VK2

Use: Purging Materials for injection molding machine

Restriction on Use: If you want to use it for any purpose other than the recommended use, seek expert judgment.

Supplier's Details:

Company Daicel Miraizu Ltd.

Address 12 Fujicho, Hirohata-ku, Himeji, Hyogo 671-1123, Japan

Section in charge Hirohata R&D Center
Phone number +81-79-238-1209
Fax number +81-79-238-1241
Emergency phone +81-79-238-1209

Section 2: Hazard Identification

Important Hazards and Effects:

Physical and chemical hazards

- Dust may cause dust explosion.

Potential health effects

- Polymer particulates may be inhalation-hazardous.

- Gases and fumes evolved during processing may irritate the respiratory tract, skin and eyes.

Specific hazards

- Hot molten material can cause thermal burns in contact with skin.

GHS Classification:

Physical and chemical hazards

Flammable solids
 Self-reactive substances and mixtures
 Classification not possible
 Distribution of possible

3. Pyrophoric solids Not classified

4. Self-heating substances and mixtures
 5. Substances and mixtures which, in contact with water, emit flammable gases

Classification not possible

6. Oxidizing solids
Classification not possible
Classification not possible
Classification not possible

Health hazards

1. Acute toxicity (oral) Not classified

2. Acute toxicity (dermal) Classification not possible

3. Acute toxicity (gases)

Not classified

4. Acute toxicity (vapours)5. Acute toxicity (dusts and mists)Classification not possible

6. Skin corrosion/irritation Not classified
7. Serious eye damage/eye irritation Not classified

8. Respiratory sensitization

9. Skin sensitization

Classification not possible

Classification not possible

10. Germ cell mutagenicityNot classified11. CarcinogenicityCategory 112. Reproductive toxicityNot classified

13. Effects on or via lactation Classification not possible

14. Specific target organ toxicity (Single exposure)
15. Specific target organ toxicity (Repeated exposure)
16. Aspiration hazard
Not classified
Not classified

Environmental hazards

Hazards to the aquatic environment (acute)
 Hazards to the aquatic environment (chronic)
 Not classified

3. Hazard to the ozone layer Classification not possible

GHS Label Elements: Pictograms



Signal words Danger

Hazard statements May cause cancer.

Precautionary statements

Prevention

- Read the Safety Data Sheet (SDS) before handling the material. Do not handle until all safety precautions have been understood.
- Use protective gears when you handle the material.
- Provide a local ventilation system in the processing room.
- Avoid release to the environment.
- Use appropriate fire extinguisher in case of fire.

Response

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- IF ON SKIN: Wash with plenty of water.

Storage

- Protect from sunlight. Store away from heat, open flames and all ignition sources.

Disposal

- Dispose of contents and container should be in accordance with applicable laws and ordinances.

Section 3: Composition/Information on Ingredients

Substance/Mixture:

Mixture

Ingredients:

Styrene-acrylonitrile copolymer(SAN)

Others (Trade Secret)

Filler

Composition:

SAN Equal to or greater than 65 mass percent

Cothers Less than 5 mass percent

Less than 30 mass percent

* Trade secret as to precise ratio of ingredients.

Hazardous Ingredients/Impurities, which are within the meaning of the GHS, and are present above cut-off level:

Styrene Less than 0.3 mass percent

Quarts Less than 0.25 mass percent

Published Reference No. of Gazette (Japan):

SAN:6-126

CAS No:

SAN:9003-54-7

Section 4: First-Aid Measures

Inhalation:

If inhaled a volume of vapors or gases of the hot molten material, remove victim to fresh air and keep at rest. Get medical attention in case having coughs, breathing or other difficulties.

Skin Contact:

Wash with water. Get medical attention in case of suffering from eczema. If contacted with condensates of gases evolved from the hot molten material, wash thoroughly with soapy water. If contact with the hot molten material, cool in clean water and get medical attention.

Eye Contact:

Rinse eyes with plenty of water immediately. Rubbing eyes may cause irritation or injure the cornea. Remove contact lenses, if present and easy to do. Get medical attention in case of any abnormalities.

Ingestion:

No acute toxicity if swallowed. If large amount swallowed, get medical attention.

Section 5: Fire-Fighting Measures

Extinguishing Media:

Water, carbon dioxide, dry chemical, foam

Specific Hazards arising from the Chemical:

The material may produce intense heat, dense black smoke, toxic fumes of gases containing carbon dioxide, carbon monoxide and nitrogen/phosphorus/halogen compounds on combustion.

Special Protective Actions for Fire-Fighters:

Fire-fighters should be equipped with self-contained breathing apparatus and wear proper protective equipment (helmet with face shield, bunker coats, gloves and rubber boots).

Section 6: Accidental Release Measures

Personal Precaution, Protective Equipment and Emergency Procedures:

Spilled material may cause slippage. Collect and dispose them with proper protective gears on if spilled.

Environmental Precautions:

Spills and releases of the material might cause environmental pollution. Immediate and full recovery should be done if accidentally spilled or released.

Methods and Materials for Containment and Cleaning Up:

Shovel and sweep up spills and releases, or use industrial vacuum cleaner. Put them into container for disposal.

Second Accident Prevention Measure:

Eliminate heat, open flames and all ignition sources nearby.

Section 7: Handling and Storage

Handling:

Technical measure

- Wear protective gears to avoid burn on molding process.
- Wear protective gears to avoid contact in eyes or on skin, and to avoid inhalation, whenever gases, fumes or dusts are generated on handling or processing. Local ventilation may be recommended.

Hygienic measure

- Gases and fumes evolved during processing may irritate the respiratory tract and skin, large amount of them might cause nausea and headache in certain people. Avoid inhalation.
- Do not bend head/hands to the nozzle/dies during processing. The hot molten materials may be splashed due to evaporation of absorbed moisture. Installation of splash prevention cover to the processing machines is recommended. Pay attention especially at around the higher limit of the temperature range. The higher the temperature is, the readilier the material splash occurs.

Precautions for safe handling

- Molten material under high temperature may decompose and produce hazardous gases and may ignite at worst when left in air uncooled, so cool it down (for example, in water) immediately.
- Molten material inside the heating unit (for example, heating barrel of injection machine) under high temperature may produce hazardous gases when left for a time, so be careful.
- Dust emerged from cutting, sanding, grinding or other mechanical processing may cause dust explosion with static discharge or electrical sparks. Keep work places clean to avoid accumulation.

Storage:

Conditions for safe storage

- Protect from sunlight. Keep away from heat, open flames and all ignition sources. Take precautionary measures against static discharge. Protect from water and moisture. Avoid overload to prevent collapse of cargos.

Specific designs for vessels

- No information is available.

Section 8: Exposure Controls/Personal Protection

Control Concentration:

Not established.

Tolerable Concentration:

Not established. The figures shown below can be used for reference.

Japan Association of Industrial Health (2014) Class 3 dust

TWA respirable 2 mg/m³
TWA total 8 mg/m³
PNOS (Particle Not Otherwise Specified)
TLV-TWA respirable 3 mg/m³
TLV-TWA total 10 mg/m³

ACGIH (2012)

Engineering Measure:

Gases and fumes may be evolved during processing at high temperature, therefore, installation of local ventilation is recommended.

Respiratory Protection:

Dust respirator should be worn in mechanical processing or sanding of moldings that may cause dust. In high gases/fumes concentration area, a chemical cartridge respirator (for organic chemicals) should be worn.

Hand Protection:

Use adiabatic gloves in handling molten material.

Eye Protection:

Use protective goggles in operations that may cause dust.

Skin and Body Protection:

Wear clothes with long sleeves in handling hot molten material.

Section 9: Physical and Chemical Properties

Physical State: Solid in granular shape

Colour: Indefinite (the colour differs depening on the colour

number)

Odour: Odourless (normal temperature)
Melting Point/Freezing Point: Shows no definite melting point.

Flammability: May catch fire
Upper/Lower Flammability or Explosive Limits: No information
Flash Point: No information
Auto-Ignition Temperature: No information
Solubility: Insoluble in water
Vapour Pressure: No information
Relative Density: Approx.1.3

Particle Characteristics: Polymer particles might form explosive gas mixture

Section 10: Stability and Reactivity

Reactivity:

The material does not react with water.

Chemical Stability:

Stable in normal storage and handling.

Possibility of Hazardous Reactions:

No information

Conditions to Avoid:

Handling and storage near heat, open flames and all ignition sources. Storage under sunlight.

Incompatible Materials:

None

Hazardous Decomposition Products:

The material may produce dense black smoke, toxic fumes of gases containing carbon dioxide, carbon monoxide and nitrogen/phosphorus/halogen compounds on combustion.

Section 11: Toxicological Information

Acute Toxicity (Oral):

No data available

Acute Toxicity (Dermal):

No data available

Acute Toxicity (Gases):

No data available

Acute Toxicity (Vapours):

No data available

Acute Toxicity (Dusts and Mists):

No data available

Skin Corrosion/Irritation:

No data available (Gases/fumes evolved during drying/processing may be irritative.)

Serious Eye Damage/Eye Irritation:

No data available (Gases/fumes evolved during drying/processing may be irritative.)

Respiratory Sensitization:

No data available

Skin Sensitization:

No data available

Germ Cell Mutagenicity:

No data available

Carcinogenicity:

No data available

Reproductive Toxicity:

No data available

Effects on or via Lactation:

No data available

Specific Target Organ Toxicity (Single Exposure):

No data available

Specific Target Organ Toxicity (Repeated Exposure):

No data available

Aspiration Hazard:

No data available

Section 12: Ecological Information

Toxicity:

No data available

Persistence and Degradability:

No data available

Bioaccumulative Potential:

No data available

Mobility in Soil:

No data available

Hazard to the ozone layer:

No data available

Other adverse effects:

Never be abandoned or dumped in any ocean or water area in order to prevent marine animals and birds from ingesting.

Section 13: Disposal Consideration

Dispose of the material and its container should be in accordance with applicable laws and ordinances.

Section 14: Transport Information

The material is not classified as dangerous/hazardous substance/mixture under any international transport regulations by road, rail, sea or air.

UN Number:
UN Proper Shipping Name:
UN Transport Hazard Class:
UN Packing Group:
Not classified
Not classified
Not classified

Environmental Hazards: Not classified as marine pollutant substance/mixture according to

the IMDG Code.

Special Precautions for users:

- Secure the containers firmly to prevent collapse of cargos.
- Avoid wetting or rough handling to prevent the containers from damage.
- Spilled material may cause a slipping hazard, therefore, collect them immediately if spilled.

Section 15: Regulatory Information

Domestic Regulation(Japan):

The Fire Defense Law

- Designated as Flammables (3,000kg or above in storage).

Poisonous and Deleterious Substances Control Law

- Not designated as poisonous nor deleterious substances.

Pollutant Release and Transfer Register (PRTR Law)

- The material(s) does not contain any relevant substances.

Industrial Safety and Health Law (Article 57-2)

- The products contain the following chemical substances subjected to notification.

Styrene (No.323)

Quarts (No.165-2)

Wastes Disposal and Public Cleaning Law

- Industrial Waste (Waste Plastics)

SDS No: G_F125009_E_HP6

Foreign Exchange and Foreign Trade Law

- Goods relevant to row 16 of appended Table 1 of Export Trade Control Order.

International Regulation:

The material is not subject to the Montreal Protocol on Substances that Deplete the Ozone Layer, the Stockholm Convention on Persistent Organic Pollutants nor the Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Section 16: Other Information

Disclaimer:

- The information herein has been prepared on the basis of the materials, information, and data available at the time being drawn up. The information may be revised with subsequently acquired knowledge. Normal handling has been presupposed for the precautionary items. Safety measures appropriate to application and usage should be taken in special handling or usage.
- User is solely responsible for decision of applying the information herein in usage of the appropriate products.
- This SDS is the English version translated from the Japanese SDS which is prepared for domestic
- The Japanese SDS is prepared according to JIS Z 7252 (2019) and JIS Z 7253 (2019) which is based upon UN GHS (Sixth revised edition).

References:

- Manual for Preventing the Discharging of Resin Pellets / Japan Plastics Industry Federation, May 1993
- 2. Prevention of dust explosion / Technology Institution of Industrial Safety, November 1983
- 3. Website of the Ministry of Health, Labor and Welfare